

GCS GaAs PIN Photodiodes for 5Gb/s 1x4, 1x8, 1x12 Array Applications



850 nm GaAs PIN PD

- Mesa Diode on Semi-Insulating Substrates
- Anode/Cathode Bonding Pads on Front Side
- Low Dark Current & Capacitance with High Responsivity
- Customer Specified Configurations Available

P/N: Do136_70um_G5_1x4,8,12	
PHYSICAL	Typical
Aperture Dia.	70 μm
Bonding Pad Dia.	75 μm x 90 μm
Die Height	150 μm
Die Size	(1-3 mm) X 400 μm
Substrate	Semi-Insulating

Applications

- 850nm 5G 1x4, 1x8, 1x12
- Infiniband
- SONET/SDH
- Unsealed 85 R.H./85C Qualified



Key Benefits

- Low-Cost 4-inch Manufacturing
- Fast Cycle-Times
- CAD Support & Mask Procurement
- Robust Process

Mask ID: Do136 (70 μm)						
CHARACTERISTICS	Conditions	Min.	Typical	Max	Unit	Notes
Bandwidth	-3V	-	5	-	GHz	
Wavelength Range	-3V	760	850	860	nm	
Responsivity	-3V	0.5	0.6	-	A/W	@ 850nm
Dark Current	-3V	-	0.1	0.5	nA	
Reverse Breakdown	-20V	-	-	1	μA	
Capacitance	-3V	-	0.25	0.28	pF	